PATENT Atty Docket No.: 200311282-1

App. Ser. No.: 10/797,152

IN THE CLAIMS

Please find below a listing of all of the pending claims. The status of each claim is set

forth in parentheses. This listing will replace all prior versions, and listings, of claims in the

present application.

1. (Currently Amended) A method of searching for at least one of a service path and a

service node operable to provide a requested service via a multicast tree, the method

comprising:

receiving a request for at least one service; [[and]]

searching stored information at a node receiving the request for at least one of a

service path and a service node operable to provide the requested service; and

searching the stored information to identify a plurality of service nodes operable to

provide the requested service in response to a service path not existing that is operable to

provide the requested service, and

wherein the information is stored in the node by

receiving location information for the plurality of nodes;

receiving information associated with services provided by the plurality of

nodes; and

storing the location information and the information associated with services.

2. (Previously Presented) The method of claim 1, wherein the stored information

comprises a global information table, the global information table including at least the

location information and the information associated with services provided for nodes in a

distributed hash table overlay network.

3. (Original) The method of claim 2, wherein the distributed hash table overlay network

is a logical representation of a physical network including the multicast tree.

4. (Original) The method of claim 3, wherein the global information table includes

information for nodes physically close in the physical network.

5. (Original) The method of claim 1, wherein searching stored information comprises:

searching the stored information to determine whether a service path or a service node

exists that is operable to provide the requested service and satisfy a QoS characteristic

identified in the request, the QoS characteristic being associated with delivering the requested

service.

6. (Original) The method of claim 1, wherein searching the stored information

comprises:

searching the stored information to determine whether a service path exists that is

operable to provide the requested service or is operable to provide at least one of the

requested services if a plurality of services are requested.

7. (Original) The method of claim 6, wherein searching the stored information to

determine whether a service path exists comprises:

searching the stored information to determine whether a service path exists that is

operable to provide the requested service and is within a predetermined distance to a node

requesting the service.

(Canceled).

(Currently Amended) The method of claim [[8]] 1, further comprising:

applying a clustering algorithm to the plurality of service nodes to identify a set of

candidate service nodes from the plurality of service nodes closest to a node requesting the

service.

10. (Original) The method of claim 1, wherein the request comprises information

identifying a plurality of requested services and an order for delivering the requested services.

11. (Original) The method of claim 1, wherein the request comprises information

identifying at least one requested service and at least one OoS characteristic associated with

delivering the requested service.

12. (Original) The method of claim 1, wherein searching stored information comprises

searching stored information for at least one of a service path and a service node operable to

provide the requested service via a multicast in an application layer multicasting network.

13. (Withdrawn) A method of requesting a service in an application layer multicasting network, the method comprising:

generating a request for a service including at least one requested service and at least one QoS characteristic associated with delivering the at least one service; and

transmitting the request to a node in a distributed hash table overlay network.

14. (Withdrawn) The method of claim 13, wherein transmitting the request to a node comprises:

determining location information for a node generating the request;

hashing at least a portion of the location information to identify a node in the distributed hash table overlay network to transmit the request; and

transmitting the request to the identified node in the distributed hash table overlay network.

15. (Withdrawn) The method of claim 14, wherein determining location information comprises:

determining a first distance from the node generating the request to at least one global landmark node:

determining a second distance from the node generating the request to at least one local landmark node proximally located to the node: and

determining location information for the node based on the first distance and the second distance

PATENT

Atty Docket No.: 200311282-1 App. Ser. No.: 10/797,152

16. (Withdrawn) The method of claim 13, wherein the overlay network includes a

plurality of nodes storing information regarding location information and services provided

by the plurality of nodes in the multicast network, such that each node in the overlay network

stores location information and services provided for nodes physically close in the multicast

network.

17. (Withdrawn) The method of claim 13, further comprising:

receiving a list of a set of candidate nodes operable to satisfy the request; and

selecting one of the candidate nodes to construct a service path from a node

transmitting the request to the selected candidate node for receiving the requested service.

18. (Withdrawn) The method of claim 17, wherein selecting one of the candidate nodes

comprises:

measuring distances to each of the candidate nodes;

determining a metric associated with the at least one QoS characteristic; and

selecting one of the candidate nodes closest to the node requesting the service and

operable to satisfy the at least one QoS characteristic.

19. (Currently Amended) A method of storing information in a node in an application

layer multicast network, wherein the method comprises:

receiving location information for a plurality of nodes;

receiving information associated with services provided by the plurality of nodes; and

storing the location information and the information associated with services in a

table, wherein the location information for the plurality of nodes comprises distances

measured from each of the plurality of nodes to a plurality of global landmark nodes and to at

least one local landmark node, and the at least one local landmark node is on a routing path to

one of the global landmark nodes.

20. (Original) The method of claim 19, further wherein the at least one local landmark

node is proximally located to a respective node of the plurality of nodes.

21. (Original) The method of claim 19, further comprising:

storing a QoS characteristic associated with at least one of the plurality of nodes in the

table.

(Original) The method of claim 19, further comprising:

storing at least one of a node identifier and a service path identifier for each of the

plurality of nodes in the table.

23. (Original) The method of claim 19, wherein receiving location information for a

plurality of nodes comprises receiving location information for a plurality of nodes, the nodes

being located physically close in the network.

24. (Currently Amended) A node in a network comprising:

means for receiving a request for at least one service, and

PATENT

Atty Docket No.: 200311282-1 App. Ser. No.: 10/797,152

means for searching stored information at the node for at least one of a service path

and a service node operable to provide the requested service, and the searching further

comprises searching the stored information to identify a plurality of service nodes operable to

provide the requested service in response to a service path not existing that is operable to

provide the requested service.

25. (Original) The node of claim 24, wherein the stored information comprises a global

information table, the global information table including at least location information and

information associated with services provided for nodes in a distributed hash table overlay

network.

26. (Currently Amended) The node of claim 25, wherein the distributed hash table

overlay network is a logical representation of a physical network-including the multicast tree.

27. (Original) The node of claim 26, wherein the global information table includes

information for nodes physically close in the physical network.

28. (Currently Amended) The node of claim 24, further comprising:

wherein the means for searching in response to a service path not existing further

comprises searching the stored information to identify a plurality of service nodes operable to

provide the requested service in response to one of a service path not existing that is operable

to provide the requested service and a the service path not existing that is operable to provide

гурр. Зет. 140.. 10/757,132

the requested service and that is operable to provide at least one predetermined QoS

characteristic.

29. (Original) The node of claim 28, further comprising:

means for applying a clustering algorithm to the plurality of service nodes to identify

a set of candidate service nodes from the plurality of service nodes closest to a node

requesting the service.

30. (Withdrawn) A computer system comprises:

a processor operable to determine a physical location of the computer system in a

peer-to-peer network by determining distances to at least one global landmark node and at

least one local landmark node proximally located to the computer system in the peer-to-peer

network; and

a memory operable to store location information and information identifying service

provided for a plurality of nodes in the peer-to-peer network.

31. (Withdrawn) The computer system of claim 30, wherein the stored information

comprises location information and information identifying service provided for a plurality of

nodes physically close in the peer-to-peer network.

32. (Withdrawn) The computer system of claim 31, wherein the processor is operable to

hash the location information to identify a node in the overlay network to transmit the

location information.

PATENT

Atty Docket No.: 200311282-1

App. Ser. No.: 10/797,152

33. (Withdrawn) The computer system of claim 32, further comprising a network

interface operable to transmit the location information to the identified node in the overlay

network.

34. (Withdrawn) The computer system of claim 31, wherein the processor is operable to

search the memory to identify a service path or a service node operable to provide a requested

service in a multicast network using the peer-to-peer network.

35. (Currently Amended) Computer software embedded on a computer readable medium,

the computer software comprising instructions performing:

receiving a request at anode for at least one service, [[and]]

searching stored information at the node for at least one of a service path and a service

node operable to provide the requested service; and

searching the stored information to identify a plurality of service nodes operable to

provide the requested service in response to a service path not existing that is operable to

provide the requested service.

36. (Currently Amended) The computer software of claim 35, further comprising

instructions performing:

wherein the searching the stored information to identify a plurality of service nodes

operable to provide the requested service in response to one-of-a service path not existing that

is operable to provide the requested service and further comprises performing the searching

for the plurality of service nodes in response to both [[a]] the service path not existing that is operable to provide the requested service and that is operable to provide at least one

predetermined QoS characteristic.

37. (Original) The computer software of claim 36, further comprising instructions

performing:

applying a clustering algorithm to the plurality of service nodes to identify a

set of candidate service nodes from the plurality of service nodes closest to a node requesting

the service.